

# P1500S

## Surface Mount Housing With Vented Base



### P1500S

Inside Dimensions: H: 14.1" X W: 10.0" X D: 5.25"



P1500S Side View



P1500S Front View



P1500S with Gasket

## Features

4 Entry Ports: Two 3/4" & Two 1" diameter • Vented base • Equipment mounting holes • 2 Base Knockouts • Dual snap lid locks • Large Inner cavity allows ample room to work in • FTTP, FTTH, Telecom, CATV or custom applications • UV Stabilized, Flame Retardant Polymer

## Options

4 Port Placement Available at Top (for Indoor Use Only) or Bottom of Housing • Gasket Seal • Override lock, custom security screw, F81 lock or self tapping screw • Conduit Adapters, Grommets • 3 Available Polymer Types • Flame Retardant Rigid or Softer Non-flame Retardant Polymer • Network Equipment is Isolated From Customer Access Using Dual Compartment Option

*\* Custom hardware and private labelling are available by special order*

**PRIMEX**  
MANUFACTURING LTD.  
[www.primex.ca](http://www.primex.ca)

**USA**  
Ph: 360-332-3100  
Fax: 360-332-3200

**CANADA**  
Ph: 604-881-7875  
Fax: 604-881-7835

**TOLL FREE**  
USA & CANADA  
Ph: 1-877-881-7875  
Fax: 1-877-881-7835